

Ridge-It Anchor

Part #	Length	Description
00500	9¾"	Ridge-It Anchor w/1 D-ring
00510	17½"	Ridge-It Anchor w/2 D-rings
00515	22"	Ridge-It Tile Anchor w/1 D-ring

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable. Contact customer service for details.

Ridge-It Anchor is suitable for the following applications:



Personal Fall Arrest: Ridge-It Anchors may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: Ridge-It Anchors may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.



Materials: stainless steel, zinc-plated steel, and butyl.

Fasteners: 3" stainless steel spiral nails.

#00500 and #00510: 8 provided nails. #00515: 12 provided nails.

MAXIMUM 1 connection per Ridge-It Anchor.

* Part # 00511 is no longer available. Part #00510 now incorporates all previous features of part # 00511, including butyl strips and flat D-rings.

UPC-A Codes: 00500: 672421005003; 00510: 672421005106; 00515: 672421005157