


# CLASS B DIABLO 2.5 CABLE SRL-LE

## SELF-RETRACTING LIFELINE

TECHNICAL DATA & SELL SHEET - ISSUE 1



**QUICK BRACKET**  
Installs easily under webbing, leaving D-ring free.

**DUAL LEG UNIT ALSO AVAILABLE**  
Allows for 100% tie-off.

**INTERNAL SHOCK ABSORBER**  
Acts as cushion between the housing & the worker to increase comfort.

**CABLE LIFELINE**  
Resists cuts & abrasions.

**CLASS B SRL**  
Reduces nuisance lockup & lowers arresting force.

**PROTECTED SHOCK PACK COVER**

**LIGHTWEIGHT COMPOSITE HOUSING**

**RUBBER STOPPER**  
Allows for easier access when connected to rear D-ring.

**RUBBER GRIP**  
Ergonomic handle for increased comfort.

**SNAP HOOK**  
Several connector types available.

**PERSONAL, NON-REPAIRABLE SRL**

11100 shown

**Lifeline:** 8', 3/16" Galvanized Steel Cable  
**Hook:** Galvanized Steel & Aluminum  
**Capacity for LE:** 130-310 lbs.  
**Housing:** High-Strength ABS  
**Capacity for Non-LE:** 130-420 lbs.

FOR MORE INFO, PLEASE CALL 1.800.466.6385 OR VISIT [GUARDIANFALL.COM](http://GUARDIANFALL.COM)

# CLASS B DIABLO 2.5 CABLE SRL-LE

## SELF-RETRACTING LIFELINE

TECHNICAL DATA & SELL SHEET - ISSUE 1

### Standards

- OSHA 1910
- OSHA 1926 Subpart M
- ANSI Z359.14-2014
- ANSI A10.32-2012



#### Performance:

- Class B SRL
- Maximum Users: 1
- Length: 8'
- LE-Use Clearance Requirements: 13'-17'
- Non-LE-Use Clearance Requirements: 9'
- Average Arrest Force: 900 lbs.

#### Notes:

- Always maintain 100% tie-off
- For dual leg kit, assemble and use according to instructions provided with dual SRL bracket
- If using with rebar hook configuration, SRL must always be worn at harness dorsal D-ring. Rebar hooks must only be connected to compatible structural rebar

### Applications



**Personal Fall Arrest:** Diablo 2.5 Cable SRL-LEs may be used in Personal Fall Arrest applications to support a maximum of 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Free fall, LE Use: Maximum 5'. Please note that free fall in excess of 2' is not in compliance with ANSI A10.32-12 fall protection regulations, but is still fully compliant with all applicable ANSI Z359.14-14, OSHA 1926 Subpart M, and OSHA 1910 regulations. Free fall, non-LE Use: Maximum 2'.



**Restraint:** Diablo 2.5 Cable SRL-LEs may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. May only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, & Shoulder.

### HOOK TYPES



Prod. Code	Description	Length
11100	Class B Diablo 2.5 Cable SRL-LE with a Steel Snap Hook	8'
11101	Class B Diablo 2.5 Cable SRL-LE with a Aluminum Snap Hook	8'
11102	Class B Diablo 2.5 Cable SRL-LE with a Steel Rebar Hook	8'
11103	Class B Diablo 2.5 Cable SRL-LE with a Aluminum Rebar Hook	8'
11104	Class B Double Diablo 2.5 Cable SRL-LE with Steel Snap Hooks	8'
11105	Class B Double Diablo 2.5 Cable SRL-LE with Aluminum Snap Hooks	8'
11106	Class B Double Diablo 2.5 Cable SRL-LE with Steel Rebar Hooks	8'
11107	Class B Double Diablo 2.5 Cable SRL-LE with Aluminum Rebar Hooks	8'

FOR MORE INFO, PLEASE CALL **1.800.466.6385** OR VISIT **GUARDIANFALL.COM**