

BUCKET OF SAFE-TIE

SAFETY KITS

FOR MORE INFO, PLEASE CALL

1.800.466.6385 OR VISIT GUARDIANFALL.COM

FEATURES & BENEFITS:

- Polydac rope for the VLA does not absorb water
- Shock pack reduces worker fatigue
- 18" lanyard extension keeps positioning device within reach and reduces trip hazards
- Includes the Velocity Harness -the best entry level harness on the market.
- Temper anchor comes with screws and nails, as well as off-set holes so it doesn't split the roof trusses
- Comes with bi-lingual instructions



SPECS

STANDARDS:

OSHA 1926 SUBPART M & 1910 / ANSI Z359.1-07 & A10.32-12

MATERIAL:

STEEL, POLYESTER, AND NYLON

CAPACITY:

130 - 310 LBS.

NUMBER OF USERS:

1 PER BUCKET OF SAFE-TIE

REMINDERS:

- ALWAYS READ AND UNDERSTAND ALL EQUIPMENT-SPECIFIC INSTRUCTIONS.
- CUSTOM CONFIGURATIONS AVAILABLE. CONTACT CUSTOMER SERVICE FOR DETAILS.

DESCRIPTION: VELOCITY HARNESS (01700), TEMPER ANCHOR (00455), & VLA-50' (01320)

PART #: 00815

WEIGHT: 15 LBS

QUANTITY: 36 PER PALLET

BUCKET OF SAFE-TIE IS SUITABLE FOR THE FOLLOWING APPLICATIONS:



PERSONAL FALL ARREST:

Bucket of Safe-Tie may be used in Personal Fall Arrest applications to support:

- Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs
- Maximum free fall is 6'.
- Applicable D-ring: Dorsal.



RESTRAINT:

Bucket of Safe-Tie may be used in Restraint applications. Restraint systems:

- Prevent workers from reaching the leading edge of a fall hazard.
- Always account for fully deployed length of the lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs.
- No vertical free fall is permitted.
- May only be used on surfaces with slopes up to 4/12 (vertical/horizontal).
- Applicable D-rings: Dorsal, Chest, Side, Shoulder.